



SPECIFICATIONS

Product Description: **8" (20.3cm) AIR BAG BLOWER SYSTEM**
 Part Number: **9535-08, 9535-08L**
 Style: **AXIAL FAN 8" (20.3cm)**

GENERAL DESCRIPTION:

8" (20.3cm) blower system with ducting is built into a heavy duty bag. Zippered ends allow blower use without removing from bag. Combination Axial 8" (20.3cm) blower, 15' (4.57m) or 25' (7.62m) duct and custom storage bag to house the system. Certified to CSA Standard C22.2 No 113.



CONSTRUCTION:

- Lightweight, metal 8" (20.3cm) blower
- Super quiet
- Carry handle with molded-in 2-speed switch
- Steel/powder coated housing and grills
- Unique bag with openings for plug/cord, inlet and outlet
- Durable reinforced polyester bag
- Easy to carry and store
- All-in-one unit for ease of operation
- Duct mounted on the blower and stored inside bag
- Both carrying handle and shoulder strap allows for easy transportation

MOTOR:

HP: 1/4 HP
 Certifications: UL Recognized, CSA Certified
 Voltage/Hz: 115V AC, 60 Hz, Single Phase
 Max RPM: 3300 (loaded at 120 Volts, 60 Hz)
 Amps: 1.4A
 Cord: 6' (1.82m) AWG
 Switch: 2-speed on/off switch
 Plug: NEMA 5-15P 125V

FAN:

- Polypropylene seven blade fan

DUCTING:

- Single-ply lightweight vinyl/polyester, PVC coated 180°F (82.2°C) temperature resistant
- Non-collapsible retractable design
- Yellow with black wear-strip and integrated nylon attachment strap on one end

DIMENSIONS:

Length In (cm)	Width In (cm)	Height In (cm)	Weight Lbs (Kg)
27" (68.5)	15" (38.1)	12" (30.4)	25 (11.3)

FLOW RATES: (free air calculated at blower)

760 CFM (1291.2 m³/hr)

AVAILABLE:

9535-08 8" (20.3cm) blower system with 15' (4.57m) ducting
 9535-08L 8" (20.3cm) blower system with 25' (7.62m) ducting